

11/Spec
DE
12/10/03
OK
Filer
2-12-04
L.A.G.

SUBSTITUTE SPECIFICATION

TITLE: HEADPHONES WITH INTEGRATED MICROPHONES

INVENTOR(S): RONALDUS M. AARTS

SERIAL NO.: 09/739,513

ATTY. DOCKET NO.: PHN 17,814

HEADPHONES WITH INTEGRATED MICROPHONES

BACKGROUND OF THE INVENTION

Field Of The Invention

[0001] The invention relates to a sound reproducing system comprising headphones with sound generating means and means for
5 controlling the sound signal generated by said headphone sound generating means to simulate external sound sources.

[0002] The invention also relates to a headphone for a sound reproducing system.

10 Description Of The Related Art

[0003] Headphones are used in and for audio equipment, such as (mobile) CD-players, but also in call-in centers.

[0004] The headphones comprise a means for generating sound (usually a small loudspeaker). A recorded sound signal (voice or
15 music) is sent to the headphone(s) and sound generators inside the headphone generate a sound. The listener will, however, perceive the generated sound as being generated inside or very near the listener's head (which in fact it is), unless the sound signal is adapted. Such a sound is perceived to be unnatural. It is known to
20 process the signals such that the perception of the sound signal by the listener is such that he/she believes to hear external sound sources, i.e., the listener perceives a more natural sound. To achieve this, the signals are processed through a filter set to

alter the characteristics of the signal such that the sound generated near, or within, the head simulates an (or more than one) external sound source(s). An important aspect in this respect is the transfer characteristics of sound by an external source to the head and the pinnae of the ear itself, the so-called Head Related Transfer Function (HRTF), i.e., the manner in which sound becomes attenuated and altered by the head and pinna itself before it actually is heard. Attempts to process the signals taking into account the HRTF to obtain external source simulation, are known from J. Acoust. Soc. Am. 85(2), pages 858-878, F.L. Wightman and D. Kistler, Feb. 1989: 'Headphone simulation of free-field listening I and II'.

[0005] Such attempts, however, do not always prove to be successful. The HRTF is dependent on the actual shape and form of the head and the ear and differs substantially from one person to another. Furthermore, head movements complicate matters as they also influence the sound perception.

[0006] Japanese patent application JP 08/079900 A discloses providing the headphones with measuring devices to measure the distance between the ears, the height of the head and head movements. Although such measurements can be used to improve the sound reproduction, the results leave room for improvement. The HTRF is a strongly individual one which can only be approximately determined using the result of such measurement. Likewise the effect of head movements can only be approximately determined.

SUMMARY OF THE INVENTION

[0007] It is an object of the invention to provide a sound system as described in the opening paragraph with improved sound reproduction.

5 [0008] To this end, the system is characterized in that the headphones are provided with microphones, and the means for controlling comprises, or is coupled to means for regulating the sound production by the headphone sound generating means such that a signal registered by the microphones is substantially zero when
10 at least one external sound source is operative in response to a signal, and means for recording the results of said regulating to influence external source simulating sound generation in the headphones and/or means for regulating the sound production by the headphone sound generating means, such that the difference between
15 a signal registered by the microphones and a known signal is substantially zero, and means for recording the results of said regulation to influence external sound simulating sound generation in the headphones.

[0009] Each headphone is provided with a microphone. The
20 microphone, which is located near or preferably in the ear, registers the sound generated by the headphone sound generating means as well as, in one aspect of the invention, by the at least one external source. The system comprises means for regulating the sound production by the headphone sound generating means such that
25 the microphone registers a substantially zero signal when,

simultaneously, at least one external source, in response to a signal, and the headphone sound generating means are active. The headphone then generates a, as far as the human perception is concerned, same auditive signal but of opposite sign as the external source(s). The system includes means for recording the results of the regulation. Thereafter, when the external source(s) (is) are shut off, or removed altogether, the sound perceived by the listener is the same as that for the external sources. The signal registered by the microphone will be equivalent to that when only the source would be operative. The relation between a signal sent to the source, such as a loudspeaker, and the signal sent to the headphone sound generating means to simulate such an external source, is then known. The data from the above-mentioned regulation are used for regulation of the sound signal to the headphones in such manner that the external source is simulated.

[0010] The relation between a signal sent to an external source; a signal sent to the headphone sound generating means and a microphone signal are thus measured. Such measurement does, however, not only give the relation between signals a (external source signal) and b (equivalent headphone signal), but also between signals b (headphone signal) and c (microphone signal) and signals a (external source signal) and c (microphone signal). These known relations can also, or separately, be used in another aspect of the invention as follows.

[0011] Once, for a 'standard head' or, in fact, for any head, the relations between signals a, b and c have been established, it is not, in all circumstances, i.e., for other heads, necessary to make further use of an external source with signal a. It suffices
5 to know (and this is known) the microphone signal c corresponding to a particular external source signal a to regulate headphone signal b, if needed. When the headphone sound generating means 'truly' (signal b) simulates an external source (signal a), a particular microphone signal (signal c) should be registered. This
10 is the case on the 'standard head'. However, when the headphone is put on another head, the HRTF will be different and the same signal b sent to the headphone sound generating means will generate a microphone signal c' different from the particular microphone signal c because of the different HRTF. The system has means for
15 regulating the signal b sent to the headphone sound generating means (to b') in such manner that signal c' is equal to signal c, for recording the regulation data, and for using the regulation data for further sound production to simulate external source(s).

[0012] It should be noted that while, in embodiments, the
20 headphone sound generating means and the microphone will be often separate elements, in some embodiments, the headphone sound generating means (headphone loudspeakers) may double in function as the microphone, especially when such headphone sound generating means is placed inside the ear channel.

[0013] Preferably, the system also comprises means for storing the regulation data for a specific person.

[0014] This enables regulation data to be kept and coupled to a specific user. The next time this user uses the system, an incoming
5 signal is filtered in the 'right' or at least 'nearly right' manner.

[0015] These and other objects of the invention will be apparent from and elucidated with reference to the embodiments described hereinafter.

10

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] In the drawings:

[0017] Fig. 1 illustrates, schematically, how to generate, from two real sound sources, a third so-called phantom source;

15 [0018] Fig. 2 illustrates, schematically, a system in accordance with the invention;

[0019] Fig. 3 illustrates, schematically, a further embodiment of a system in accordance with the invention;

20 [0020] Fig. 4 illustrates yet a further embodiment of a system in accordance with the invention;

[0021] Fig. 5 illustrates a still further embodiment of a system in accordance with the invention;

[0022] Fig. 6 illustrates another aspect of the invention;

25 [0023] Figs. 7A to 7E illustrate several embodiments of a headphone for a system in accordance with the invention; and

[0024] Fig. 8 illustrates, schematically, how the headphone sound generating means may be also the microphone.

[0025] The figures are schematic and not drawn on scale.

5 DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0026] Figure 1 shows a head of a person 1 with two ears 2 and 3. Two real loudspeakers LS_L (loudspeaker-left) and LS_R (loudspeaker-right) are present in a room. With these loudspeakers, it is meant to generate a sound as if a sound signal V_r is
10 generated by a loudspeaker LS_p at some other point in space.

[0027] To calculate which signals have to be generated by the real loudspeakers LS_L and LS_R to give the person 1 the impression that the sound he/she hears is generated by a (phantom) sound source LS_p generating a signal X , the signal X has to be altered,
15 i.e., filtered by filter function W_{XL} (l for left) for loudspeaker LS_L and by W_{XR} for loudspeaker LS_R .

[0028] Thus, the signal emitted by loudspeaker LS_L is XW_{XL} , and the signal generated by LS_R is XW_{XR} .

[0029] A signal generated by a sound source, be it real or
20 phantom, causes (for real sources), or is supposed to cause (for phantom sources), at an ear, a pressure equivalent to the signal multiplied by a transfer function. The transfer function W_{ll} (left loudspeaker to left ear), W_{lr} (left loudspeaker to right ear), W_{rl} (right loudspeaker to left ear), W_{rr} (right loudspeaker to right

ear), W_{p1} (phantom loudspeaker to left ear) and W_{pr} (phantom loudspeaker to right ear) are indicated in the figure.

[0030] The sound pressure P_l at the left ear caused by loudspeakers LS_l and LS_r is the sum of the sound pressure XW_{xl}

5 (signal to left loudspeaker) * W_{l1} (transfer function left loudspeaker to left ear) + XW_{xr} (signal to right loudspeaker) * W_{r1} (transfer function right loudspeaker to right ear). Thus:

$$P_l = X(W_{xl}W_{l1} + W_{xr}W_{r1}).$$

10

Likewise, the sound pressure P_r at the right ear equals

$$P_r = X(W_{xl}W_{lr} + W_{xr}W_{rr}).$$

15 The sound pressure which would be caused by the phantom loudspeaker is:

(left ear)	$P'_l = XW_{p1}$
(right ear)	$P'_r = XW_{pr}$

20

Substituting $P_l = P'_l$ and $P_r = P'_r$, leads to:

$$W_{xl} = (W_{p1}W_{l1} - W_{pr}W_{r1}) / (W_{l1}W_{rr} - W_{lr}W_{r1})$$

25

$$W_{xr} = (W_{p1}W_{lr} - W_{pr}W_{rr}) / (W_{lr}W_{r1} - W_{l1}W_{rr})$$

[0031] The filter functions, which, in this simplified model, have been described, actually have to be determined for each frequency, thus, actually, for each frequency, a filter function W_{XR} and W_{XL} has to be determined, fixed and used. With the proper filter
5 functions W_{XR} and W_{XL} , the listener hears the 'phantom source' LS_p . Thus, with two loudspeakers, a 'phantom' sound source at a sound can be generated which, to the listener, seems to come from another location than the actual location of the loudspeakers LS_L and LS_R . This perception is dependent on the accuracy of the transfer
10 functions (in this application sometimes also called 'filters' or 'filter settings') W_{XL} and W_{XR} .

[0032] The filters W_{XL} and W_{XR} are difficult to determine because the transfer functions W_{1l} , W_{1r} , W_{rr} and W_{lr} from the loudspeakers LS_l and LS_r to the ear are difficult to determine. The transfer
15 function for the real loudspeakers, to some extent, can be calculated and/or measured for a 'standard head', but, in reality, each head and each headphone is different, and thus, a transfer function is always more or less appropriate, but never really good. The transfer functions for the phantom source can only be estimated
20 or theoretically derived. Especially for the higher frequencies, the transfer functions are difficult to determine because of the shape of the head and the ear canal. In short, the Head Related Transfer function, HRTF, is a highly individual one.

[0033] The transfer function needs to be calculated, and the
25 calculation introduces errors.

[0034] For each frequency, the transfer function has to be determined, which either requires a large calculation effort and such calculation in itself may be a source of error, or necessitates the use of average transfer functions for a band of
5 frequencies, which also introduces errors.

[0035] All transfer functions are, to some extent, dependent not just on the relative positions of the sound sources (real or phantom) and the ears, but also on other factors, such as objects near the sources or ears which may reflect or alter the sound
10 waves, and thus, influence the transfer functions.

[0036] Thus, there is a need to improve the sound reproduction.

[0037] Figure 2 illustrates a preferred embodiment of a system in accordance with the invention.

[0038] The system comprises two headphones each of which is
15 provided with a microphone 6, 7. Each of the headphones has sound generating means 4, 5. A signal $x(k)$ is relayed to the means 4, 5 through filter means (i.e., modulation means) 8, 9 having filter setting $W_{XL}(k)$ and $W_{XR}(k)$. In previous systems, the filters 8, 9 were fixed filters (as in Figure 1) and thus, the settings $W_{XL}(k)$ and
20 $W_{XR}(k)$ were fixed. These fixed filters were usually set to be equivalent to an 'average head' in an 'average room'. The signals after the filters are indicated with $\hat{e}_l(k)$ and $\hat{e}_r(k)$. The signals are $\hat{e}_l(k) = x(k) * W_{XL}(k)$ and $\hat{e}_r(k) = x(k) * W_{XR}(k)$. In the system in accordance with the invention, microphones 6 and 7 are present in
25 or near the headphones, and generate signals $r_l(k)$ and $r_r(k)$. The

signals $r_1(k)$ and $r_2(k)$ result from the sum of the sound generated by the external source and the headphone. These signals $r_1(k)$ and $r_r(k)$ are fed to respective comparison and regulation means 10 which also have respective inputs for signal $x(k)$ and respective outputs to filter means 8, 9 for adapting or regulating settings $W_{XL}(k)$ and $W_{XR}(k)$. It should be noted that in Figure 2, only the transfer functions W_{11} and W_{rr} are shown. This will be explained below.

[0039] A signal $x(k)$ is supplied to the sound source PL and signals $\hat{e}_1(k)$ and $\hat{e}_r(k)$ are supplied to the sound generating means 4 and 5. The signals $r_1(k)$ and $r_r(k)$ are fed to the regulating means 10. This regulating means influences the settings of the filters $W_{XL}(k)$ and $W_{XR}(k)$ (and thereby the signals $\hat{e}_1(k) = x(k) * W_{XL}(k)$ and $\hat{e}_r(k) = x(k) * W_{XR}(k)$) until the microphone signals $r_1(k)$ and $r_r(k)$ (and this preferably for each, or for a chosen set or selection of frequencies) become substantially zero. This may be done by a step-wise manner, i.e., one or more parameters (one or more of the settings $W_{XL}(k)$ or $W_{XR}(k)$) is (are) changed, it is then checked whether the signal $r_1(k)$ is increased or decreased, if it is increased, the parameter(s) is (are) changed in the opposite sense, if it is decreased, the parameter(s) is (are) changed in the same sense. This process is repeated until the signals $r_1(k)$ and $r_r(k)$ are substantially zero. For more details of such methods, reference is made to, e.g., 'Adaptive Filter Theory' by Simon Haykin, Prentice Hall, Upper Saddle River, ISBN 0-13-322760-X. It is to be

noted that, in general, the less parameters have to be taken into account in such methods, the better the result is and the faster the result can be achieved. When the microphone signals $r_r(k)$ and $r_l(k)$ are substantially zero, the listener hears nothing. The

5 resulting values for filter settings $W_{XL}(k)$ and $W_{XR}(k)$ are thereby determined. These filter settings can be, for instance, tables in a computer database. When the source PL is shut off or removed, the listener will hear a sound which, to the listener, is perceived to come from said source PL. Thus, the listener hears a 'phantom

10 source' at the position of source PL. If the system is to be used for one person only, such tables could be the only one to use, but, preferably, the system comprises means (schematically indicated by input I in Figure 2) for storing established settings $W_{XL}(k)$ and $W_{XR}(k)$ for the filters 8, 9, and matches the settings to data

15 identifying the person. The next time that same person uses the system, the filter will then be set correctly, or at least nearly correctly, for that person, provided information identifying the person is given to the system. In practice, tables are, for instance, stored in a computer database matched with a name or

20 number identifying the person.

[0040] Compared to previous methods and devices, the results are better and much more reliable, i.e., a much more 'natural' sounding and better 'localized' phantom source is heard by the listener. An advantage over fixed filters is that W_{XL} and W_{XR} can easily, faster

25 and with much greater accuracy be determined and be adapted for

different locations and for different persons. For instance, if head transfer functions are calculated with fixed filters, often parameters, such as, an average height and width of an average head, are used. Such parameters are sometimes useless or may even
 5 give clearly wrong results if the person in question is wearing some head ware, such as, a hat or, for instance, has a size head substantially different from the average head. Even the height of the person's hair may be of importance in this respect.

Furthermore, more parameters than inter ear distance and head
 10 height may be of importance for the HRTF. The present invention does not suffer from these shortcomings but gives reliable results for each person, irrespective of the size and shape of the head and/or ear and/or whether said person wears a hat, because all of these factors do not play a role due to the microphone.

15 Furthermore, the cross transfer functions (W_{rl} and W_{lr}) are, due to the nearness of the source 4, 5 to the ear 2, 3, negligible or, in any case, very small. This enables, in preferred embodiments, as, e.g., shown in Figure 2, to further greatly simplify the calculation, thus removing a source of error. In formula form, it
 20 holds:

$$W_{XL} = (W_{pl}) / (W_{ll})$$

$$W_{XR} = (W_{pr}) / (W_{rr})$$

25

[0041] These formulae are much simplified compared to formulae for phantom sound generation using loudspeakers with fixed filters. For each ear, the filter functions are only dependent on two, not six, transfer functions. In fact, the determinations of the filter settings W_{XR} and W_{XL} are independent. The measurement at the left (right) ear suffices to determine $W_{XL}(k)$ ($W_{XR}(k)$). This enables faster (less response time) and much better determination of W_{XL} and W_{XR} . Furthermore, the response of the acoustic paths of the headphones is very short (thus further shortening response time). Furthermore, extraneous influences, such as, the shape of a room and objects in a room, on the transfer functions W_{11} , W_{rr} (and W_{r1} , W_{1r}) are not present in headphone sound reproduction. As a consequence, when tests were done with a system as schematically shown in Figure 2 to see what the perceived difference would be between the real loudspeaker and a phantom loudspeaker, the location of the phantom loudspeaker was correct for both an anechoic room (a room in which sound reflection is reduced to a minimum) and a listening room (a room with normal sound reflection). These results were much better than those for known systems using fixed filters. As an alternative (and this may be in particular of importance for source at a relatively large distance) instead of working with a signal coming from each microphone, the sum ($r_1(k)+r_r(k)$) and difference ($r_1(k)-r_r(k)$) of these two signals could also be used. If the sum and the difference are zero, both signals are zero. Usually W_{11} and W_{rr} are nearly equal (symmetric),

and, at large distances from the source W_{pl} and W_{pr} , are also not too much different. These facts are preferably used to simplify the calculations. It should be noted that in Figure 2, the different filter means (8, 9) and regulation means (10) are drawn separately
5 to increase clarity. They may be, and preferably are, all integrated in one device. In certain circumstances, for instance, a nearly symmetrically arranged fixed position of the source, only one microphone may be used. The data of said one microphone would then suffice.

10 [0042] Figure 3 illustrates a further embodiment of a system in accordance with the invention. Two loudspeakers PL_1 and PL_2 are used. For both loudspeakers, the transfer functions W_{XL} and W_{XR} can be determined in the manner as described above. This can be done in the following manner. First, loudspeaker PL_1 is activated and
15 microphone signals are made zero. The filter settings $W_{XL}(k)$ and $W_{XR}(k)$ for said loudspeaker are determined. Thereafter, loudspeaker PL_1 is deactivated and loudspeaker PL_2 is activated to determine filter settings $W'_{XL}(k)$ and $W'_{XR}(k)$ for loudspeaker PL_2 . The filter functions for both loudspeakers having been determined, the system
20 is capable of reproducing any mix of the two sound sources PL_1 and PL_2 with a very natural sound, i.e., stereo sound.

[0043] For a signal $x(k)$ sent to loudspeaker PL_1 and, simultaneously, a signal $y(k)$ sent to loudspeaker PL_2 , the signals to the headphone sound generating means are:

$$\hat{e}_1(k) = x(k) * W_{XL}(k) + y(k) * W'_{XL}(k) \text{ and}$$

$$\hat{e}_r(k) = x(k) * W_{XR}(k) + y(k) * W'_{XL}(k).$$

[0044] When more than two sources are to be simulated, the
5 signals to the more than two sources could, for instance, be
written as a vector and the filter settings for the different
sources could be written in matrix form. Multiplication of the
vector (for the sources) with the matrix (for the settings) will
generate the signals $\hat{e}_1(k)$ and $\hat{e}_r(k)$. The matrix itself is
10 determined by measurements and may be different for different
persons and different rooms.

[0045] A further embodiment of the system in accordance with the
invention is shown in Figure 4. Having established the transfer
functions W_{XL} and W_{XR} , respectively, W'_{XL} and W'_{XR} for two loudspeakers
15 PL_1 and PL_2 , this knowledge can be used to 'create' using, for
instance, geometrical principles more phantom sound sources, for
instance, phantom loudspeakers PL_3 and PL_4 . Using, for instance,
thereafter, the above technique of vector-matrix multiplication, a
'surround sound' may be created. The problem with trying to do so
20 using fixed filters lies, as already explained, among others, in
the very individual Head Related Transfer Functions and also from
local circumstances, such as, reverberation in a room. Starting
from two known sources, one can, using geometry and/or standard
techniques, calculate the transfer function for the phantom sources
25 PL_3 and PL_4 in so far as geometry is concerned but not or much less

the other influences. In a system in accordance with the invention, said difficulty is resolved for the main part, since use is made of actual measurements on an actual head with actual headphones (thus, taking into account the relevant HRTF) and in an actual room (thus
5 at least partly taking into account the reverberation in the room) resulting in transfer functions which take these influences in account giving much better rendition of phantom sources.

[0046] A yet further embodiment is shown in Figure 5. The headphones (or at least one of them, or the connection between the
10 headphones) comprise means for measuring the position with respect to the two sources PL_1 and PL_2 and/or some fixed reference point. Such means can be, for instance, infra-red sources which are sensed by sensors in or near the sources PL_1 and PL_2 or infra-red sources in or near PL_1 and PL_2 which are sensed by sensors in the
15 headphones. Such means may also comprise means for generating and sensing ultra-sound. In this example, the two 'real' loudspeakers are positioned at either side of a television set 51. Near or at least at one headphone, an emitter of a signal or sensor for localization signals is present and a stationary part of the system
20 comprises a sensor or emitter for localization signals.

[0047] As explained before, the transfer functions are determined using the microphones 6 and 7 and when the two sources PL_1 and PL_2 are turned off, they are then audible in the headphones as 'phantom sources'. The transfer functions to simulate these two
25 external sources PL_1 and PL_2 then include the individual HRTF and

room-related factors. Knowing the position of the head and the filter, using geometric considerations, one or more phantom sources PL_3 and PL_4 can be created, or alternatively or in addition, the system may comprise tables with many transfer functions for many different positions of the listener vis-a-vis the sources. As the listener moves in the room, the position of the head vis-a-vis the sources PL_1 and PL_2 is regularly measured and used to create phantom sources PL_1 to PL_4 at the right places. The 'proper' filter functions may then be established either by, for instance, choosing a filter setting table associated with a position most nearest to the actual position or taking some average (for instance, by interpolation) of several filter settings corresponding to several positions close to the actual position. In establishing the 'proper filter functions' for real or phantom sources, use may be made of the fact that human ear is much more perceptible to sound coming from positions in front of the head, than to the back of the head. In other words, to create a 'surround sound', it is not necessary to have a number of sources equally distributed around the listener, i.e., the number of sources to the back of the head may be less.

[0048] The examples given so far all start with determining filter functions W_{XL} and W_{XR} for one or more loudspeakers (or channels) phantom or real by regulating the signal $\hat{e}_l(k)$, $\hat{e}_r(k)$ sent to the headphone sound generating means 4, 5 such that the signal $r_l(k)$, $r_r(k)$ measured by the microphone(s) is substantially zero

when a signal $x(k)$ is sent to a source PL_1 , PL_2 and extracting filter setting data $W_{XR}(k)$, $W_{XL}(k)$ from said measurement.

[0049] Figure 6 illustrates a different aspect of the invention. In this particular aspect, an external source has been used to find
5 the filter settings W_{XL} and W_{XR} for a particular head, which, for simplicity, will be called a 'standard head'. These filter settings are, however, as explained, dependent on the very individual HRTF. For other persons, these settings may not be correct. As explained above, one way of overcoming this problem is to measure the filter
10 functions for any individual person and store the filter function setting coupled with data identifying said person. However, although such procedure gives excellent results, this is a rather complicated procedure. In an aspect of the invention, a different route is followed. When the filter settings for a 'standard head'
15 are correct (i.e., the microphone signal due to the sum of the sound of an external source and the microphone sound generating means due to a signal $x(k)$ is zero), the external source is shut off, and a microphone signal $r''(k)$ due to signal sent to the headphone sound generating means is measured (or alternatively the
20 headphone sound generating means are shut off and the microphone signal due to the external source is measured). Data corresponding to the signal $r''(k)$ are stored in the system. When another person puts on the headphones, the very same signal $x(k)$ will generate with the same filter setting the same signal $\hat{e}_1(k)$ sent to the
25 headphone sound generating means 4, but a microphone signal $r'(k)$

which differs, due to a difference in HRTF, from the stored signal $r''(k)$. In Figure 6, it is schematically illustrated that the system, in this aspect of the invention, comprises means for comparing the signal $r'(k)$ to the signal $r''(k)$ and means 10 for changing the filter settings $W_{XL}(k)$ and $W_{XR}(k)$ (the latter not being shown, for simplicity) such that a comparison between a signal registered by the microphones ($r'(k)$) and a known or calculated signal ($r''(k)$, $r'''(k)$, $r''''(k)$) show said two signals to be substantially the same. A comparison of the signals or data 10 representing the signal $r'(k)$ and $r''(k)$ then shows that the signals are substantially the same. Such a comparison can be done in different ways. The most simplest is to store data for $r''(k)$ and to calculate the sum or difference (depending on the sign of the stored data) of the data for $r'(k)$ and $r''(k)$. These data may 15 directly represent the signal $r'(k)$ and $r''(k)$ or be some data derived from the signals, such derivation being done to reduce the data needed for comparison. For instance, the signals $r'(k)$ and $r''(k)$ may be converted into Fourier space and the comparison may be done in Fourier space. The filter settings are then recorded 20 (for instance, in means 8, 9 or 10, but they could also be recorded in some other means) and they are used for further sound production to simulate an or more external source(s). It should be noted that, apart from the shape and size of the head, also other factors may be of importance, for instance, the acoustics (reverberations, for 25 instance) of the site at which the sound was generated. In Figure

6, $r''(k)$ may, for instance, correspond to sound reproduction in a concert hall, $r'''(k)$ to sound reproduction in a stadium, and $r''''(k)$ to sound reproduction in a small room (chamber or club). The user of the system may choose such settings, to his/her liking.

5 In this example, the comparison signal $r''(k)$ etc. are fixed signals corresponding with fixed situations. In a more sophisticated system, the comparison signal could be more freely chosen, for instance, by giving the user the opportunity to change the size and acoustic characteristics of the virtual site or the
10 position of the listener within the site. The basic idea is that the signal $r'(k)$ (and such for each channel) is compared to a stored or computer-generated signal (be it $r''(k)$, $r'''(k)$, $r''''(k)$) and that the two signals are made substantially the same by changing the filter settings $W_{XR}(k)$, $W_{XL}(k)$.

15 [0050] Figures 7A to 7E illustrate several embodiments of a headphone for a system in accordance with the invention.

[0051] In Figure 7A, a tube 12 is attached to the microphone 6 of headphone 11, the tube 12 being inserted in the inner ear. In this embodiment, in which the headphone 11 has a shell-like
20 construction with the sound generating means inside the shell, it is preferred that the microphone registers the sound in the inner ear near the eardrum. For this purpose, the tubes 12, as sound guides, are provided. In Figure 7B, the headphone is placed inside the ear and the microphone 6 near or in the inner ear. In Figure
25 7C, the headphone 11 and microphone 6 are separate devices but both

placed in or near the ear. The output signal of the sound generating means is fed to a jack 72, the output signal of the microphone is fed to a separate jack 71. In Figure 7E, both output signals are fed to a single jack 73 which has two separate ports 75 and 76 through which the signals may be transferred to a part of the system. This embodiment is the most preferred embodiment, because one single jack is necessary. The part of the sound system in which the jack will be inserted may be provided with means for picking up the signals. Such a jack can be a standard jack, but for the extra output, likewise, the part of the sound system in which the jack will be inserted may be standard, but for the possibility of registering the signal from the microphone. This enables 'standard' equipment, at least as far as the user is concerned, to be used. The sound system will be able to operate with 'normal headphone' (in which case there will be no microphone signal), but will be able to register whether or not a headphone in accordance with a system of the invention is used, and if so, operate in accordance with the invention.

[0052] Figure 7D illustrates that the signal ($r_1(k)$, $r_r(k)$ or any combination of derivative of or data representing said signals) from the microphone can be relayed wirelessly as well as by a separate plug.

[0053] It will be clear that within the framework of the invention, many variations are possible.

[0054] For instance, in the above given examples, the microphone is shown as an element separate from the other elements. In other embodiments, the headphone sound generating means may itself be used as microphone. Figure 8 illustrates very schematically how this can be done. Headphone sound generating means 81 comprises or is coupled to or with a means 82 for driving a membrane 83 to generate sounds. Said system is supplied with a signal I_{in} via an input 84. The headphone sound generating means also comprises means 85 (which may have some, most or even all building elements common to means 82) with an output 86 which generates a signal I_{out} corresponding to the movement of the membrane. A means 87 for regulating the signal I_{in} has an input for signal I_{out} and regulates I_{in} such that I_{out} becomes substantially zero when an external source generates a sound I . In these circumstances, the sound pressure at the position of the membrane is zero; thus it is silent. Preferably, for these embodiments, i.e., for the embodiments wherein the headphone sound generating means double in function as microphones, the headphone sound generating means are, in operation, located inside the ear.

[0055] In short; the invention can be described as follows:

[0056] A sound reproduction system comprises headphones (11). Said headphones comprise means for generating sound (4, 5) and microphones (6, 7) (i.e., means for recording sound). Further, the system comprises filter means (8, 9) for filtering a signal such that the sound produced simulates external sound sources. These

filter means comprise filter setting data $W_{XR}(k)$, $W_{XL}(k)$. The system comprises a feed-back and control system (10) in which signals $(r_1(k), r_r(k))$ from the microphones (6, 7) are used to set the settings $W_{XL}(k)$, $W_{XR}(k)$ of the filter means (8, 9). The signals can
5 be used by making them zero (when an external source is used) $(r_1(k)=0)$, see Figure 3) or by comparing the microphone signals and a gauge signal zero $(r''(k)-r'(k)=0)$, see Figure 6) such that the two are substantially the same.

[0057] It should be noted that systems are known, for instance,
10 for use in very high noise environments, such as airports, to cancel noise. In some of such systems, a microphone inside the headphone is used. The headphone sound generating means make a counter-noise to cut out or at least strongly reduce all noise within a certain frequency bandwidth. The idea behind such systems
15 is that by eliminating the usually low frequency noise, the noise to signal ratio between the noise and the usually more high frequency communication sounds signals is increased. Such systems, however, do not simulate external sources nor are the microphone signals used to set filter settings.

20